



| | | |
|-----------------------------|-----------------|------|
| DESIGN STANDARD/设计标准 | JIS F 7209-1996 | |
| TEST/检验 | JIS F 7200-1996 | |
| HYDRAULIC INSPECTION/压力试验 | | |
| TEST PRESSURE / 试验压力 Mpa | DODY / 强度 | 0.74 |

| DN | d | L | D | C | NO. | h | l | H |
|--------|-----|-----|-----|-----|-----|----|----|-----|
| 5k50 | 50 | 140 | 130 | 105 | 4 | 15 | 16 | 405 |
| 10K50 | 50 | 140 | 155 | 120 | 4 | 19 | 20 | 405 |
| 5K65 | 65 | 170 | 155 | 130 | 4 | 15 | 18 | 495 |
| 10K65 | 65 | 170 | 175 | 140 | 4 | 19 | 22 | 495 |
| 5K80 | 80 | 185 | 180 | 145 | 4 | 19 | 18 | 525 |
| 10K80 | 80 | 185 | 185 | 150 | 8 | 19 | 22 | 525 |
| 5K100 | 100 | 210 | 200 | 165 | 8 | 19 | 20 | 651 |
| 10K100 | 100 | 210 | 210 | 175 | 8 | 19 | 24 | 651 |

| 序号 | 零件名称 | 材料 | NAME OF PART | MATERIAL |
|------|------|--------------------------|-----------------------------------|-----------------|
| 5 | o形圈 | 丁腈橡胶 | O-ring | |
| 4 | 滤网 | Q235A(内有1CF18N1911不锈钢丝网) | Strainer | SS400 (SUS 304) |
| 3 | 支架 | QT450 | Cover push | FCD400 |
| 2 | 阀盖 | HT200 | BONNET | FC200 |
| 1 | 阀体 | HT200 | BODY | FC200 |
| 油过滤器 | | | Shipbuilding-Simplex oil strainer | |



青岛威固船用阀门制造有限公司

Qingdao V-Goal Marine Valve Manufacturing Co., Ltd.